



Website: <http://www.airsan.com>
Email: contactus@airsan.com

4554 West Woolworth Avenue
Milwaukee, WI 53218

Phone (414) 353-5800 or (800) 558-5494
Fax (414) 353-8402

TYPE CF DRY-PLEAT FILTER ELEMENTS

For Engines, Air Compressors and Blowers





AIRSAN TYPE CF REPLACEMENT FILTER ELEMENTS


Airsan Type CF is a highly efficient Dry-Pleat filter element designed for use on engines, air compressors and blowers. Type CF elements are 98% efficient on 3 micron particles and 100% on 10 micron particles. Pressure drop is held to a minimum. Polyester media insures easy cleaning, requires no adhesive and allows effective use at temperatures up to 300°F (148.9 Celsius)

AIRSAN TYPE CF REPLACEMENT FILTER ELEMENTS

(Shipped complete with pre-filter blanket)

Catalog Description	Filter Element Part Number	Element Dimensions (Inches)			Capacity CFM	Weight Lbs.
		O.D.	I.D.	Height		
CF 8-01	901620	8	4	8	185	4
CF 8A-01	901621	8	4	12	280	6
CF 10-01	901622	10	6	15	420	8
CF 12-01	901623	12	8	18	580	10
CF 14-01	901624	14	10	21	800	15
CF 18-01	901625	18	10	18	1085	20
CF 18A-01	901626	18	10	27	1630	22
CF 22-01	901627	22	14	22	1890	25
CF 22A-01	901628	22	14	33	2835	45
CF 24-01	901629	24	16	36	3500	50
CF 28-01	901630	28	20	39	4780	60
CF 32-01	901631	32	24	39	5700	65
CF 36-01	901632	36	28	39	6650	80

CF filter elements are available with molded end caps – contact factory for details.



Panel Filters

Airsan Panel Filters are manufactured in a variety of media and sizes to meet your filtration requirements. These included galvanized steel, stainless steel, bronze, aluminum, monel, polyester, paper and foam.



Replacement Filter Elements

Airsan Type C oil wetted multi-crimped elements are highly efficient, designed for use on blowers, engines and air compressors. Type C filters eliminate 93% of dust and dirt while pressure drop is held to only 0.15" to 0.25" clean.



Oil Wetted Intake Filters

Airsan Type CH filters are designed for air intakes on compressors, blowers and engines. Filter housings are equipped with various sizes of MPT pipe to be mounted directly to the unit. CH filters use Airsan Type C filter elements.



Website: <http://www.airsan.com>
Email: contactus@airsan.com

4554 West Woolworth Avenue
Milwaukee, WI 53218

Phone (414) 353-5800 or (800) 558-5494
Fax (414) 353-8402